

Colorful
innovations



AluNaturElox

Personal anodizing colors with natural elegance

The Elox series is a new AluNatur color range that complements our AnoMax product range with a semi transparent substitute that shows up the natural beauty of the aluminium.

AluNatur Elox is available in Transparent Lacquering (TL) and Brushed aluminium substrates ranging from 0.5 up to 1.5 mm thickness. Whether you want to match EURAS industrial standards or other anodizing standards, all is possible in our new Elox series.



AluNatur PUR-PA
Elox Anodized Brushed
90F1054.10



AluNatur PUR-PA
Elox Champagne BRUSHED
90F3061.30



AluNatur HDP
Elox Light Umber BRUSHED
90R2967.60



AluNatur HDP
Elox Medium Champagne BRUSHED
90R2966.60



AluNatur PUR-PA
Elox Pale Umber BRUSHED
90F2968.10





AluNatur PUR-PA
Elox Umber TL
90F2969.10

Benefits

- Shows up the natural beauty of the aluminum
- Transparent Lacquering (TL) and Brushed versions
- Flexibility for bending & roll forming (no stress whitening)
- Multiple gloss levels
- Personal anodizing according to any standard
- Price economy



EURAMAX

	AnoMax	AluNaturElox
Versions	AnoMax AnoMax ultra matt 	AluNatur PUR-PA AluNatur HDP 
Substrates	Aluminum 0.3 - 2.0 mm	Aluminum 0.5 mm - 1.5 mm
Appearance	Metallic/ pearlescent	Transparent on Brushed or TL (Transparent Lacquering) aluminum substrates
Gloss	10-30	10-90
Quantity	≥ 450 m1	≥ 450 m1 if on stock Minimum quantities apply for these aluminum substrates. Please contact Euramax for volumes < 5 tonnes
Typical applications	Aluminum composite panels Metal sandwich panels Profiled sheets Insulated panels Single skin cassettes Steel sandwich panels	Aluminum composite panels Metal sandwich panels Profiled sheets Insulated panels Single skin cassettes
Colors	Acc. Euras, Anolok, Alnecolan, etc.	Acc. Euras, Anolok, Alnecolan, etc. Only very dark colors are not possible
Guidelines	<ul style="list-style-type: none"> • Install panels in same direction to avoid reflection differences • Order projects in one batch to avoid color differences • www.euramax.eu/anomax 	<ul style="list-style-type: none"> • Bare material may slightly vary in color / show up small irregularities • Final coated product can slightly vary from sample • Protective film recommended to avoid installation scratches • End use > 1500 meters from coastal area • No end use in heavy industrial / corrosive environments • Limited end use between 30° NL and 30° SL • www.euramax.eu/alunaturelox

Contact our **Architectural Support**
for information or samples:
T +31 (0)475 370 341
E max@euramax.eu
I www.euramax.eu



EURAMAX